

1. Identification

| | |
|---|--|
| Product identifier | MLC™ Hydrated Lime - Verona |
| Other means of identification | |
| Product code | High Reactivity Hydrated Lime, Standard Hydrated Lime, and Calcium Hydroxide |
| CAS number | 1305-62-0 |
| Recommended use | Industrial, Chemical, Construction, Environmental and Water Treatment applications of calcium hydroxide. |
| Recommended restrictions | Not for food or food contact applications. |
| Manufacturer/Importer/Supplier/Distributor information | |
| Manufacturer: | Mississippi Lime Company d/b/a MLC |
| Address: | 16147 US Highway 61 Ste Genevieve, MO 63670 |
| Phone Number: | (800) 437-5463 |
| 24 Hour Emergency Contact Number: | (866) 519-4752 |
| Access code: | 336393 |

2. Hazard(s) identification

| | | |
|------------------------------|--|---|
| Physical hazards | Not classified. | |
| Health hazards | Skin corrosion/irritation | Category 2 |
| | Serious eye damage/eye irritation | Category 1 |
| | Specific target organ toxicity, single exposure | Category 3 respiratory tract irritation |
| Environmental hazards | Hazardous to the aquatic environment, acute hazard | Category 3 |
| OSHA defined hazards | Not classified. | |
| Label elements | | |



| | |
|--|---|
| Signal word | Danger |
| Hazard statement | Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. Harmful to aquatic life. |
| Precautionary statement | |
| Prevention | Avoid breathing dust. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear eye protection/face protection. Wear protective gloves. |
| Response | If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. |
| Storage | Store in a well-ventilated place. Keep container tightly closed. Store locked up. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | None known. |
| Supplemental information | None. |

3. Composition/information on ingredients

Substances

| Chemical name | Common name and synonyms | CAS number | % |
|--|--------------------------|------------|----------|
| Calcium hydroxide (Ca(OH) ₂) | | 1305-62-0 | 90 - 100 |

Impurities

| Chemical name | Common name and synonyms | CAS number | % |
|-------------------|--------------------------|------------|-----|
| Calcium carbonate | | 471-34-1 | ≤ 5 |
| Magnesium Oxide | | 1309-48-4 | < 4 |
| Silicon dioxide | | 7631-86-9 | ≤ 2 |

Composition comments Occupational Exposure Limits for impurities are listed in Section 8. All concentrations are in percent by weight.

4. First-aid measures

| | |
|---|--|
| Inhalation | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Call a poison center or doctor/physician if you feel unwell. |
| Skin contact | Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. |
| Eye contact | Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Skin irritation. May cause redness and pain. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Use water spray to cool unopened containers. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | The product is nonflammable and does not support combustion. |

6. Accidental release measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|--|--|

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Prevent product from entering drains. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage**Precautions for safe handling**

Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not get this material in contact with eyes. Avoid breathing dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection**Occupational exposure limits****U.S. - OSHA Impurities**

| Material | Type | Value |
|---------------------------------|------|----------|
| Silicon dioxide (CAS 7631-86-9) | TWA | 80 mg/m3 |

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

| Material | Type | Value | Form |
|--|------|----------|----------------------|
| Calcium carbonate, synthetic (CAS 1305-62-0) | PEL | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |

Impurities

| Material | Type | Value | Form |
|---------------------------------|------|----------|--------------------|
| Magnesium Oxide (CAS 1309-48-4) | PEL | 15 mg/m3 | Total particulate. |

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

| Material | Type | Value | Form |
|--|------|----------|----------------------|
| Calcium carbonate, synthetic (CAS 1305-62-0) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |

Impurities

| Material | Type | Value | Form |
|---------------------------------|------|----------|----------------------|
| Silicon dioxide (CAS 7631-86-9) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 20 mppcf | |

Magnesium Oxide (CAS 1309-48-4)

| Type | Value | Form |
|------|----------|----------------------|
| TWA | 5 mg/m3 | Respirable fraction. |
| | 15 mg/m3 | Total dust. |
| | 50 mppcf | Total dust. |
| | 15 mppcf | Respirable fraction. |
| | 15 mppcf | Respirable fraction. |

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

| Impurities | Type | Value | Form |
|----------------------------------|------|----------|----------------------|
| Calcium carbonate (CAS 471-34-1) | TWA | 5 mg/m3 | Respirable fraction. |
| | | 15 mg/m3 | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |

US. ACGIH Threshold Limit Values (TLV)

| Material | Type | Value |
|--|------|---------|
| Calcium carbonate, synthetic (CAS 1305-62-0) | TWA | 5 mg/m3 |

| Impurities | Type | Value | Form |
|---------------------------------|------|----------|---------------------|
| Magnesium Oxide (CAS 1309-48-4) | TWA | 10 mg/m3 | Inhalable fraction. |

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

| Impurities | Type | Value |
|---------------------------------|------|------------|
| Silicon dioxide (CAS 7631-86-9) | IDLH | 3000 mg/m3 |
| Magnesium Oxide (CAS 1309-48-4) | IDLH | 750 mg/m3 |

US. NIOSH: Pocket Guide to Chemical Hazards

| Material | Type | Value | Form |
|--|------|----------|-------------|
| Calcium hydroxide (Ca(OH) ₂) (CAS 1305-62-0) | TWA | 5 mg/m3 | |
| | | | |
| Silicon dioxide (CAS 7631-86-9) | TWA | 6 mg/m3 | |
| | | | |
| Calcium carbonate (CAS 471-34-1) | TWA | 5 mg/m3 | Respirable. |
| | | 10 mg/m3 | Total |

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

Eye/face protection

Use tight fitting goggles.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

Skin protection

Other

Wear appropriate chemical resistant clothing.

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties**Appearance**

Physical state Solid.

Form Powder.

Color White.

Odor None.

Odor threshold Not available.

pH 12.4 In aqueous solution

Melting point/freezing point 1076 °F (580 °C)

Initial boiling point and boiling range Not available.

Flash point Does not flash

Evaporation rate Not available.

Flammability (solid, gas) Non combustible.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure < 0.0000001 kPa (77 °F (25 °C))

Vapor density Not available.

Relative density Not available.

Solubility(ies)

Solubility (water) 1.7 g/l at 20 °C

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

Density 2.2398 g/cm³ estimated

Explosive properties Not explosive.

Molecular formula Ca-H₂-O₂

Molecular weight 74.1 g/mol

Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity Reacts violently with strong acids. This product may react with oxidizing agents.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous reactions No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the decomposition temperature. Contact with incompatible materials. Do not mix with other chemicals.

Incompatible materials Acids. Oxidizing agents. Maleic anhydride. Nitroethane. Nitromethane. Nitroparaffins. Nitropropane. Phosphorus.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information**Information on likely routes of exposure**

Inhalation Dust may irritate respiratory system. Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

| | |
|---|--|
| Eye contact | Causes serious eye damage. |
| Ingestion | May cause discomfort if swallowed. |
| Symptoms related to the physical, chemical and toxicological characteristics | Skin irritation. May cause redness and pain. Dermatitis. Rash. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes. Coughing. |

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

| Product | Species | Test Results |
|--|---------|--------------|
| Calcium hydroxide (Ca(OH) ₂) (CAS 1305-62-0) | | |
| Acute | | |
| Oral | | |
| LD50 | Rat | 7340 mg/kg |

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye irritation Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Silicon dioxide (CAS 7631-86-9) 3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure May cause respiratory irritation.

Specific target organ toxicity - repeated exposure Not classified.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

| Product | Species | Test Results |
|--|--|---------------------|
| Calcium hydroxide (Ca(OH) ₂) (CAS 1305-62-0) | | |
| Aquatic | | |
| <i>Acute</i> | | |
| Fish | LC50 Zambezi barbel (Clarias gariepinus) | 33.9 mg/l, 96 hours |

Persistence and degradability The product contains inorganic compounds for which biodegradability is not applicable.

Bioaccumulative potential No data available.

Mobility in soil This product is slightly water soluble and may disperse in soil.

Other adverse effects No data available.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.

| | |
|--|--|
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. |

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) This substance is on the TSCA 8(b) inventory and is designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

Classified hazard categories Skin corrosion or irritation
Serious eye damage or eye irritation
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA) Total food additive
Direct food additive
GRAS food additive

US state regulations

US. Massachusetts RTK - Substance List

Calcium carbonate (CAS 471-34-1)
Calcium hydroxide (Ca(OH)₂) (CAS 1305-62-0)
Magnesium Oxide (CAS 1309-48-4)

Silicon dioxide (CAS 7631-86-9)

US. New Jersey Worker and Community Right-to-Know Act

Calcium carbonate (CAS 471-34-1)

Calcium hydroxide (Ca(OH)₂) (CAS 1305-62-0)

Magnesium Oxide (CAS 1309-48-4)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium carbonate (CAS 471-34-1)

Calcium hydroxide (Ca(OH)₂) (CAS 1305-62-0)

Magnesium Oxide (CAS 1309-48-4)

Silicon dioxide (CAS 7631-86-9)

US. Rhode Island RTK

Calcium carbonate (CAS 471-34-1)

Calcium hydroxide (Ca(OH)₂) (CAS 1305-62-0)

Magnesium Oxide (CAS 1309-48-4)

Silicon dioxide (CAS 7631-86-9)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|--|------------------------|
| Australia | Australian Inventory of Industrial Chemicals (AICIS) | Yes |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | Yes |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | Yes |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | Yes |
| Korea | Existing Chemicals List (ECL) | Yes |
| New Zealand | New Zealand Inventory | Yes |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | Yes |
| Taiwan | Taiwan Chemical Substance Inventory (TCSI) | Yes |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| | |
|---------------|--|
| Issue date | 03-December-2024 |
| Revision date | 03-December-2024 |
| Version # | 02 |
| HMIS® ratings | Health: 3 Flammability: 0 Physical hazard: 0 |

NFPA ratings



Disclaimer

Mississippi Lime Company cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.